

HUSKY SWIVEL • SAFE-T-BREAK® COMBINATION

FOR TRUCK AND HIGH VOLUME FUELING

Husky Model 8015 Swivel-Safe-T-Break® Combination

- Multi-plane, full 360° spherical rotation for easy movement of nozzle.
- Swivel Sync® feature to prevent separation failure in the 90° position.
- High strength step shoulder bearing diameters and impact absorbing stops.
- Dynamic seals have double o-ring construction for long life and low temperature performance.
- Separates at less than 225 lbf / 1000.9 N which minimizes backlash force of separations, reducing damage to equipment.
- Safe-T-Break® is reconnectable and retains UL listing after reconnecting.
- Dual check valves stop fuel in both directions.
- Internal pressure balancing chamber prevents “line shock” nuisance separations.
- Compatible with fuels containing up to 15% alcohol.
- Compact and light weight for easy handling.
- Easier to reconnect when installed at the nozzle.
- Eliminates the need for a whip hose.

SPECIFYING INFORMATION

Model Number	Description	Weight lbs.(kg.)
8015	1" M x 1" F Multi-Plane Swivel • Reconnectable Safe-T-Break®	1.5 (0.7)

CONSTRUCTION

Body	Aluminum, Zinc Alloy
Seals	Fluorocarbon
Springs	Stainless Steel
Threads	1" BSP

PATENTS and LISTINGS

Patent Numbers: Pending

Listings:  Pending



MADE IN THE U.S.A.



HUSKY SWIVEL • SAFE-T-BREAK® COMBINATION

FOR STANDARD FUELING APPLICATIONS

- **Dimensions**
- **Accessories**

Guards

Model No.	Description
8015	Scuff Guard for Safe-T-Break®

