

VIIIS BSPP Nozzles



Husky

GENERAL FUELING PRODUCTS

4-9

HIGH VOLUME FUELLING

Pressure activated, automatic shut-off nozzle for truck stop and other high volume full-service, self-service and unattended stations.

- VIIIS nozzle shuts off when
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Spout is reinforced with thick aluminum bushing that retains spout spring and keeps spout from rounding-in: the two leading causes of clicking off and splash-back spillage.
- Comes standard with smooth full grip guard and waffle splash guard.
- Equipped with a unique Flo-Stop™ device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.



New Nozzles

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
177638	w/ Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	3.9 (1.7)
177640	w/o Hold Open Clip, w/ Waffle Splash Guard and Spout Bushing	3.9 (1.7)

Rebuilt Heavy Duty Diesel Nozzle

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
266038	w/ Three Notch Hold Open Clip, Waffle Splash Guard and Spout Bushing	3.9 (1.7)

Construction

Body	Aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon
Lever	One piece contoured steel
Inlet	1" / 25.4 mm BSPP

