

XS DP Nozzles



Pressure Activated, automatic shut-off nozzle for full-service and self-service stations.

- XS® Nozzle shuts off when
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Double Poppet allows “to the penny” dispensing.
- Double Poppet is a two(2) step closure reducing the amount of pressure spiking, or “hydraulic hammer”, and the adverse effects this has on the hose and dispenser meter.
- Aluminum reinforced spout bushing keeps spout tip round and acts as a captive fastener to prevent tip-end sensor damage.
- Equipped with a unique Flo-Stop™ device that shuts off the nozzle if it falls from the fill tank or raises above the horizontal.
- *StreamShaper™* reduces turbulence for straighter fuel flow and less splash back spillage.
- Comes standard with smooth full grip guard.

New Unleaded Nozzles w/ NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539604	w/ Three Notch Hold Open Clip	3.1 (1.4)
539676	w/ Three Notch Hold Open Clip and Waffle Splash Guard	3.1 (1.4)

New Light Duty Diesel Nozzles w/ NPTF Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539603	w/ Three Notch Hold Open Clip	3.1 (1.4)

New Unleaded Nozzles w/ BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
539616A*	w/ Three Notch Hold Open Clip - Atex	3.1 (1.4)
539632A	w/ Three Notch Hold Open Clip and Sightglass - Atex	3.1 (1.4)
E539616	w/ Three Notch Hold Open Clip and Mate Guard	3.1 (1.4)
E539687	w/ Three Notch Hold Open Clip Flo-Equalizer™ and Mate Guard	3.1 (1.4)
E539620	w/o Hold Open Clip w/ Mate Guard	3.1 (1.4)

New Light Duty Diesel Nozzles w/ BSPP Threads

MODEL NO.	DESCRIPTION	SHIPPING WEIGHT LBS (KG)
E359615	w/ Three Notch Hold Open Clip and Mate Guard	3.1 (1.4)
E539686	w/ Three Notch Hold Open Clip Flo-Equalizer™ and Mate Guard	3.1 (1.4)



CONSTRUCTION

Body	One piece die cast aluminum
Seals	Fluorocarbon
Packing	Double o-ring seal protected by fiber reinforced Teflon
Lever	One piece contoured steel with hard plastic cover
Inlet	3/4" / 19 mm NPTF

